

Professional Series



Green
Power



Environmental
Friendly



Energy
Saving



PowerTank PRO Series

Line Interactive UPS



- Active Touch Screen LCD Display with Information on all Parameters
- Constant-FLO™ High Speed Intelligent Charger
- Built-in AVR for Voltage Stabilization
- Excellent CPU Control Guarantee High Reliability
- High Quality 12V 7AH Battery
- Off Mode Charging
- Lightning, Spike & Surge Protection
- Overload & Overheat Protection
- Modem / Fax / Tel Line / Network Protection (RJ45) *Optional
- Comes with USB Port & Power Management Software *Optional



• Boost & Buck •
AVR



• British •
Socket



• 3 Years •
Warranty

Professional Series



RIGHT POWER

The Power Of Continuity



PowerTank P850T
(Back View)

3 x British Output Socket c/w Safety Window



PowerTank P1000T/1250T
(Back View)

Circuit breaker

USB Port
(Only available for P1250T)
Modem/Fax/Network/Fax/
Phone Line Protection (RJ 45)
(Only available for P1250T)
4 x British Socket Output
c/w Safety Window

Technical Specification:

MODEL	PowerTank P 850T	PowerTank P 1000T	PowerTank P 1250T
CAPACITY (VA)	850VA	1000VA	1250VA
INPUT			
INPUT VOLTAGE	220 / 230 / 240VAC		
VOLTAGE RANGE	162 - 290Vac		
OUTPUT			
OUTPUT VOLTAGE	220 / 230 / 240VAC		
AC VOLTAGE REGULATION (Batt. Mode)	± 10%		
OUTPUT FREQUENCY (Batt. Mode)	50Hz or 60Hz ± 1Hz		
OUTPUT WAVEFORM	Simulated Sinewave		
TRANSFER TIME (Typical)	2ms - 6ms		
OUTPUT SOCKET	3 x British Output Socket c/w Safety Window	4 x British Output Socket c/w Safety Window	
BATTERY			
SEALED LEAD ACID MAINTENANCE FREE BATTERY	12V 7AH x 1	12V 7AH x 2	12V 7AH x 2
BACK UP TIME (Depending on Load)	10 - 15 minutes	30 - 40 minutes	
RECHARGE TIME	4-6 Hours to 90% After Complete Discharge		
STATUS INDICATOR			
LCD DISPLAY	Input Voltage, Output Voltage, Battery Capacity, Load Level, UPS Status		
AUDIBLE ALARM	Battery Mode, Lowe Battery, Overload, UPS Fault		
COMMUNICATION			
POWER MANAGEMENT SOFTWARE	N/A	N/A	Support Window Family, Linux, Sun Solaris, IBM Aix, Compaq True 64, FreeBSD, HP-UX, MAC
INTERFACE	USB Port		
PROTECTION			
FULL PROTECTION	Discharge, Overcharge and Overload Protection		
PHONE / FAX / MODEM / NETWORK PROTECTION	N/A	N/A	RJ 45
PHYSICAL			
OPERATING ENVIRONMENT	0-40°C, 0-90% Relative Humidity (Non-Condensing)		
NOISE LEVEL	Less Than 40dB		
DIMENSION (D x W x H) mm	300 x 101 x 142	320 x 130 x 182	320 x 130 x 182
WEIGHT (KG)	4.5	8	8
WARRANTY			
UPS WARRANTY	3 Years Full Warranty Include Parts & Labour 2 Years Warranty for Battery		

*Specification subjects to change without prior notice