



POWER LOGIC

www.KossUPS.com.my

KOSS UPS

SYLION Series 3000VA

- For Office and Multimedia PC's
- Point of Sales Terminal
- Other Office Equipment

Line Interactive UPS

- Compact size
- Touch screen LCD to display UPS information circularly
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave
- Off-mode charging
- Cold start function



NOW! 3 YEARS
FULL WARRANTY
Parts & Labour
2 Years for Battery



Malaysia



UK



USA



Korea



SYLION Series 3000VA

Line Interactive UPS

- Compact size
- Touch screen LCD to display UPS information circularly
- Excellent microprocessor control guarantees high reliability
- Boost and buck AVR for voltage stabilization
- Auto restart while AC is recovering
- Simulated sine wave
- Off-mode charging
- Cold start function



Specifications

MODEL	Sylation S-300EL
CAPACITY	3000 VA
INPUT	
Voltage	220/230/240 VAC
Voltage Range	162-290 VAC
Frequency Range	50 Hz \pm 1 Hz
OUTPUT	
Socket	British Type Socket x 4
Voltage	220/230/240 VAC
AC Voltage Regulation (Batt. Mode)	\pm 10%
Frequency Range (Batt. Mode)	50 Hz \pm 1 Hz
Transfer Time	Typical 2-6 ms
Waveform (Batt. Mode)	Simulated Sinewave
BATTERY	
Battery Type & Number	12V 9Ah x 4
Typical Recharge Time	4-6 hours recover to 90% capacity
INDICATORS	
LCD Display	Input voltage, output voltage, battery capacity, load level and UPS status
ALARM	
Battery Mode	Sounding every 10 seconds
Low Battery	Sounding every second
Overload	Sounding every 0.5 second
Fault	Continuously sounding
PROTECTION	
Full Protection	Overload, discharge, and overcharge protection
Cooling Fan	Yes
Interface	USB + RJ11/RJ45
PHYSICAL	
Dimension, D X W X H (mm)	495 x 150 x 250
Net Weight (kgs)	24.8
ENVIRONMENT	
Humidity	0-90 % RH @ 0- 40°C (non-condensing)
Noise Level	Less than 40dB

*Specification subjects to change without prior notice

www.KossUPS.com.my



ISO 9001 CERTIFIED COMPANY

